



# Automatic Transmission and Power Steering Stop Leak and Conditioner

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

MSDS Version: E07.04

Date of issue: 27/05/2016

Blend Version: 7

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Automatic Transmission and Power Steering Stop Leak and Conditioner  
Product code : W64559

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Oil additive

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Wynn's Belgium  
Industriepark-West 46  
9100 Sint-Niklaas - Belgium  
T +32 3 766 60 20 - F +32 3 778 16 56  
[msds@wynns.eu](mailto:msds@wynns.eu) - [www.wynns.com](http://www.wynns.com)

#### 1.4. Emergency telephone number

Emergency number : BIG: +32(0)14/58.45.45

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : -  
Hazard statements (CLP) : H412 - Harmful to aquatic life with long lasting effects  
EUH-statements : EUH208 - Contains alkoxyated long-chain alkyl amine. May produce an allergic reaction  
Precautionary statements (CLP) : P273 - Avoid release to the environment

#### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	% w	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified	(CAS No) 64742-65-0 (EC no) 265-169-7 (EC index no) 649-474-00-6 (REACH-no) 01-2119471299-27	75 - 90	Not classified
thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich	(CAS No) 398141-87-2 (EC no) 800-172-4 (REACH-no) 01-2119969520-35	2,5 - 5	Aquatic Chronic 2, H411
methacrylate copolymer	(CAS No) confidential	2,5 - 5	Eye Irrit. 2, H319
Alkoxy sulfolane	(CAS No) confidential	1 - 2,5	Aquatic Chronic 2, H411
Long Chain Alkyl Amine	(CAS No) confidential	0,1 - 1	Acute Tox. 4 (Oral), H302

# Automatic Transmission and Power Steering Stop Leak and Conditioner

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

			Skin Corr. 1B, H314 Aquatic Acute 1, H400
alkoxylated long-chain alkyl amine	(CAS No) confidential	0,1 - 1	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Check the vital functions. Keep victim at rest in half upright position. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Keep watching the victim. Give psychological aid. Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain. If necessary seek medical advice.
- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : May cause an allergic skin reaction.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. AFFF foam. ABC-powder.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid.
- Explosion hazard : Product is not explosive.

#### 5.3. Advice for firefighters

- Firefighting instructions : Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : No open flames. No smoking. Spill area may be slippery.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable gloves and eye/face protection.
- Emergency procedures : Mark the danger area. Seal off low-lying areas. Take off contaminated clothing and wash before reuse.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

# Automatic Transmission and Power Steering Stop Leak and Conditioner

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage. Contain leaking substance, pump over in suitable containers.
- Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Clean preferably with a detergent - Avoid the use of solvents.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Presents no particular risk when handled in accordance with good occupational hygiene practice.
- Hygiene measures : Use good personal hygiene practices. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Meet the legal requirements. Store in a closed container.
- Storage area : Meet the legal requirements. Protect from heat and direct sunlight.
- Special rules on packaging : correctly labelled. Meet the legal requirements.

### 7.3. Specific end use(s)

See product bulletin for detailed information.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

Italy - Portugal - USA ACGIH TWA (mg/m<sup>3</sup>) 5 mg/m<sup>3</sup>  
ACGIH

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)

PNEC (Oral)  
PNEC oral (secondary poisoning) 9,33 mg/kg food

#### thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11-isoalkyloxy) derivs., C10-rich (398141-87-2)

DNEL/DMEL (Workers)  
Long-term - systemic effects, dermal 44 mg/kg bodyweight/day  
Long-term - systemic effects, inhalation 3,1 mg/m<sup>3</sup>  
DNEL/DMEL (General population)  
Long-term - systemic effects, oral 0,4 mg/kg bodyweight/day  
Long-term - systemic effects, inhalation 0,8 mg/m<sup>3</sup>  
Long-term - systemic effects, dermal 22 mg/kg bodyweight/day  
PNEC (Water)  
PNEC aqua (freshwater) 0,0024 mg/l  
PNEC aqua (marine water) 0,00024 mg/l  
PNEC aqua (intermittent, freshwater) 0,24 mg/l  
PNEC (Sediment)  
PNEC sediment (freshwater) 0,435 mg/kg dwt  
PNEC sediment (marine water) 0,0435 mg/kg dwt  
PNEC (Soil)  
PNEC soil 0,086 mg/kg dwt  
PNEC (STP)  
PNEC sewage treatment plant 100 mg/l

### 8.2. Exposure controls

- Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Does not require any specific or particular technical measures.

# Automatic Transmission and Power Steering Stop Leak and Conditioner

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Personal protective equipment : Gloves. Safety glasses.



Hand protection : Neoprene. Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer.

Other information : Breakthrough time : >30'. Thickness of the glove material >0,1 mm.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light brown.
Odour	: characteristic.
Odour threshold	: No data available
pH	:
Relative evaporation rate (butylacetate=1)	: No data available
refraction index	: 1,479
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 150 °C
Auto-ignition temperature	: > 250 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density @20°C	: 877 kg/m <sup>3</sup>
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic @40°C	: 30 mm <sup>2</sup> /s
Viscosity, dynamic @40°C	: No data available
Viscosity	: 5,6 mm <sup>2</sup> /s @100°C
Viscosity Index	:
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content	: 0 %
Other properties	: Dimethylsulfoxide (DMSO) <3%.
Additional information	: The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Combustible liquid. Stable under normal conditions.

# Automatic Transmission and Power Steering Stop Leak and Conditioner

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Keep away from strong acids and strong oxidizers.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No additional information available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### **Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)**

LD50 oral rat > 5000 mg/kg bodyweight Sprague-Dawley  
LD50 dermal rabbit > 2000 mg/kg bodyweight New Zealand White  
LC50 inhalation rat (mg/l) > 5,53 mg/l/4h Sprague-Dawley

#### **Alkoxy sulfolane (confidential)**

LD50 oral rat > 10000 mg/kg bodyweight  
LD50 dermal rabbit 4000 - 8000 mg/kg  
ATE CLP (dermal) 4000,000 mg/kg bodyweight

#### **alkoxylated long-chain alkyl amine (confidential)**

LD50 oral rat 1350 mg/kg bodyweight  
LC50 inhalation rat (ppm) 220 ppm/1h  
ATE CLP (oral) 1350,000 mg/kg bodyweight  
ATE CLP (gases) 110,000 ppmv/4h

#### **Long Chain Alkyl Amine (confidential)**

LD50 oral rat 1230 mg/kg bodyweight  
LD50 dermal rabbit 8000 mg/kg bodyweight  
ATE CLP (oral) 1230,000 mg/kg bodyweight  
ATE CLP (dermal) 8000,000 mg/kg bodyweight

Skin corrosion/irritation : May produce an allergic reaction

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : This product contains hazardous components for the aquatic environment.

Ecology - water : Harmful to aquatic life with long lasting effects.

#### **Distillates (petroleum), solvent-dewaxed heavy paraffinic, Baseoil - unspecified (64742-65-0)**

LC50 fish 1 > 100 mg/l @96h Pimephales promelas  
EC50 Daphnia 1 > 10000 mg/l @48h Daphnia magna  
EC50 other aquatic organisms 1 <= 100 mg/l @72h Pseudokirchneriella subcapitata

# Automatic Transmission and Power Steering Stop Leak and Conditioner

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Remove to an authorized waste treatment plant. Avoid release to the environment.

European List of Waste (LoW) code : 12 01 12\* - spent waxes and fats  
15 01 10\* - packaging containing residues of or contaminated by dangerous substances

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

Not regulated for transport

### 14.2. UN proper shipping name

Not applicable

### 14.3. Transport hazard class(es)

Not applicable

### 14.4. Packing group

Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### 14.6.1. Overland transport

No additional information available

#### 14.6.2. Transport by sea

No additional information available

#### 14.6.3. Air transport

No additional information available

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 0 %

# Automatic Transmission and Power Steering Stop Leak and Conditioner

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 15.1.2. National regulations

Water hazard class (WGK) : 1 - low hazard to waters

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Sens. 1	Sensitisation — Skin, Category 1
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H400	Very toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
EUH208	Contains . May produce an allergic reaction

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*