



Diesel Clean 3

Safety Data Sheet

according to Regulation (EC) No. 453/2010

MSDS Version: E03.00

Date of issue: 15/01/2015

Blend Version: 3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Diesel Clean 3
Product code : W12293

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Diesel fuel additive

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Wynn's Belgium
Industriepark-West 46
9100 Sint-Niklaas - Belgium
T +32 3 766 60 20 - F +32 3 778 16 56
msds@wynns.eu - www.wynns.be

1.4. Emergency telephone number

Emergency number : BIG: +32(0)14/58.45.45

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3	H226
Eye Irrit. 2	H319
STOT RE 1	H372
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Full text of H-statements: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xn; R65
Xn; R48/20
R10
R66
R52/53

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazardous ingredients :

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hazard statements (CLP) :

H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H319 - Causes serious eye irritation
H372 - Causes damage to organs (central nervous system) through prolonged or repeated exposure

Diesel Clean 3

Safety Data Sheet

according to Regulation (EC) No. 453/2010

EUH-statements	H412 - Harmful to aquatic life with long lasting effects : EUH066 - Repeated exposure may cause skin dryness or cracking
Precautionary statements (CLP)	: P102 - Keep out of reach of children P405 - Store locked up P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P260 - Do not breathe vapours P280 - Wear eye protection P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor P331 - Do NOT induce vomiting P273 - Avoid release to the environment

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% w	Classification according to Directive 67/548/EEC
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(EC no) 919-164-8 (REACH-no) 01-2119473977-17	75 - 90	Xn; R48/20 Xn; R65 R66
4-methylpentan-2-ol	(CAS No) 108-11-2 (EC no) 203-551-7 (EC index no) 603-008-00-8 (REACH-no) 01-2119473979-13	10 - 25	R10 Xi; R36/37/38
2-Ethylhexyl nitrate	(CAS No) 27247-96-7 (EC no) 248-363-6 (REACH-no) 01-2119539586-27	5 - 10	Xn; R20/21/22 R44 N; R51/53 R66
Hydrocarbons, C10, aromatics, <1% naphthalene	(EC no) 918-811-1 (REACH-no) 01-2119463583-34	0,1 - 1	N; R51/53 Xn; R65 R66 R67

Name	Product identifier	Specific concentration limits
4-methylpentan-2-ol	(CAS No) 108-11-2 (EC no) 203-551-7 (EC index no) 603-008-00-8 (REACH-no) 01-2119473979-13	(C >= 25) Xi;R37
2-Ethylhexyl nitrate	(CAS No) 27247-96-7 (EC no) 248-363-6 (REACH-no) 01-2119539586-27	(C >= 10) R44

Name	Product identifier	% w	Classification according to Regulation (EC) No. 1272/2008 [CLP]
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(EC no) 919-164-8 (REACH-no) 01-2119473977-17	75 - 90	STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
4-methylpentan-2-ol	(CAS No) 108-11-2 (EC no) 203-551-7 (EC index no) 603-008-00-8 (REACH-no) 01-2119473979-13	10 - 25	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335
2-Ethylhexyl nitrate	(CAS No) 27247-96-7 (EC no) 248-363-6 (REACH-no) 01-2119539586-27	5 - 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Aquatic Chronic 2, H411
Hydrocarbons, C10, aromatics, <1% naphthalene	(EC no) 918-811-1 (REACH-no) 01-2119463583-34	0,1 - 1	STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Name	Product identifier	Specific concentration limits
4-methylpentan-2-ol	(CAS No) 108-11-2 (EC no) 203-551-7 (EC index no) 603-008-00-8 (REACH-no) 01-2119473979-13	(C >= 25) STOT SE 3, H335

Diesel Clean 3

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Full text of R- and H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Keep victim at rest in half upright position. Vomiting: prevent asphyxia/aspiration pneumonia. Victim in shock: on his back with legs slightly raised. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. If necessary seek medical advice.
- First-aid measures after inhalation : Call a POISON CENTER or doctor/physician if you feel unwell. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : Repeated exposure may cause skin dryness or cracking.
- Symptoms/injuries after ingestion : Harmful if swallowed. Headache. Abdominal pain. Risk of aspiration pneumonia. May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. AFFF foam. ABC-powder.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable liquid and vapour. This material can accumulate static charge by flow or agitation and can be ignited by static discharge.
- Explosion hazard : No direct explosion hazard.

5.3. Advice for firefighters

- Firefighting instructions : Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : No open flames. No smoking. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Face-shield. Gloves. protective clothing.
- Emergency procedures : Mark the danger area. Seal off low-lying areas. Large spills/in enclosed spaces: compressed air apparatus. Take off contaminated clothing and wash before reuse.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain leaking substance, pump over in suitable containers.
- Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Clean with detergents. Avoid solvent cleaners.

Diesel Clean 3

Safety Data Sheet

according to Regulation (EC) No. 453/2010

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Meets the legal requirements. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin. Presents no particular risk when handled in accordance with good occupational hygiene practice.

Hygiene measures : Use good personal hygiene practices. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Meets the legal requirements. Keep container tightly closed. Protect from sunlight. Store in a well-ventilated place.

Storage temperature : < 45 °C

Storage area : Meets the legal requirements. Keep container tightly closed in a cool, well-ventilated place. Ventilation along the floor.

Special rules on packaging : Keep only in original container. correctly labelled.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Italy - Portugal - USA ACGIH TWA (ppm) 100 ppm
ACGIH

4-methylpentan-2-ol (108-11-2)

Belgium Limit value (mg/m³) 106 mg/m³

Belgium Limit value (ppm) 25 ppm

Belgium Short time value (mg/m³) 169 mg/m³

Belgium Short time value (ppm) 40 ppm

Belgium Remark (BE) D

France VME (mg/m³) 100 mg/m³

France VME (ppm) 25 ppm

Germany TRGS 900 Occupational exposure limit value (mg/m³) 85 mg/m³

Germany TRGS 900 Occupational exposure limit value (ppm) 20 ppm

Italy - Portugal - USA ACGIH TWA (ppm) 25 ppm
ACGIH

Italy - Portugal - USA ACGIH STEL (ppm) 40 ppm
ACGIH

United Kingdom WEL TWA (mg/m³) 106 mg/m³

United Kingdom WEL TWA (ppm) 25 ppm

United Kingdom WEL STEL (mg/m³) 170 mg/m³

United Kingdom WEL STEL (ppm) 40 ppm

8.2. Exposure controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Does not require any specific or particular technical measures.

Personal protective equipment : Gloves. Safety glasses.



Hand protection : Neoprene, nitrile. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer.

Other information : Breakthrough time : >30'. Thickness of the glove material >0,1 mm.

Diesel Clean 3

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	:
Relative evaporation rate (butylacetate=1)	: No data available
refraction index	: 1,441
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 46,5 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density @20°C	: 809 kg/m ³
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic @40°C	: 1,22 mm ² /s
Viscosity, dynamic @40°C	: No data available
Viscosity	:
Viscosity Index	:
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 98,05 %
Additional information	: The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Keep away from strong acids and strong oxidizers.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours. Carbon monoxide. Carbon dioxide.

Diesel Clean 3

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Harmful: may cause lung damage if swallowed
2-Ethylhexyl nitrate (27247-96-7)	
ATE CLP (oral)	500,000 mg/kg bodyweight
ATE CLP (dermal)	1100,000 mg/kg bodyweight
ATE CLP (dust,mist)	1,500 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Causes damage to organs (central nervous system) through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: May cause long lasting harmful effects to aquatic life.
Ecology - water	: Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

4-methylpentan-2-ol (108-11-2)

Persistence and degradability Readily biodegradable in water. Biodegradable in the soil.

2-Ethylhexyl nitrate (27247-96-7)

Persistence and degradability Not readily biodegradable in water.

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Remove to an authorized waste treatment plant.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1993

14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, N.O.S.

Transport document description (ADR) : UN 1993 FLAMMABLE LIQUID, N.O.S. (methyl isobutyl carbinol), 3, III, (D/E)

Diesel Clean 3

Safety Data Sheet

according to Regulation (EC) No. 453/2010

14.3. Transport hazard class(es)

Class (ADR) : 3
Danger labels (ADR) : 3



14.4. Packing group

Packing group (ADR) : III

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 30
Classification code (ADR) : F1
Orange plates :



Special provisions (ADR) : 274, 601, 640E
Transport category (ADR) : 3
Tunnel restriction code (ADR) : D/E
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
EAC code : •3YE

14.6.2. Transport by sea

EmS-No. (1) : F-E, S-E

14.6.3. Air transport

Instruction "cargo" (ICAO) : 366
Instruction "passenger" (ICAO) : 355
Instruction "passenger" - Limited quantities (ICAO) : Y344

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions
Diesel Clean 3 is not on the REACH Candidate List
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances
VOC content : 98,05 %

15.1.2. National regulations

Water hazard class (WGK) : 2 - hazard to waters

15.2. Chemical safety assessment

No additional information available

Diesel Clean 3

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 16: Other information

Full text of R-, H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H372	Causes damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
R10	Flammable
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed
R36/37/38	Irritating to eyes, respiratory system and skin
R44	Risk of explosion if heated under confinement
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment
R65	Harmful: may cause lung damage if swallowed
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness
N	Dangerous for the environment
Xi	Irritant
Xn	Harmful

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product