



Product specifications



Consumer range

RADIATOR FLUSH

High Performance in All Coolants

Wynn's Radiator Flush is a concentrate to clean automotive cooling systems.

Properties

- ✓ Powerful acid free radiator cleaner.
- ✓ Dual action:
 1. Removes scale.
 2. Eliminates rust, deposits and oily residues.
- ✓ Excellent performance in all types of cooling liquid, including OAT coolant.
- ✓ Keeps dirt and particulates in suspension whilst cleaning.
- ✓ Safe for rubber hoses, seals and all metals in the cooling system.
- ✓ Extremely effective in all closed-circuit cooling systems.
- ✓ Restores the optimal operation of the controls within the cooling system.

Applications

- ✓ Recommended for "water" cooled systems of all petrol and diesel engines.
- ✓ Recommended for use when changing the cooling liquid (follow manufacturer's recommendations).
- ✓ Particularly effective when cleaning older cooling systems.

Technical data

Appearance	: green slightly hazy liquid
Density at 15°C	: ca. 1,071 kg/dm ³
Refractive Index at 20°C	: ca. 1,356
Freezing Point	: ca. 0°C
pH undiluted	: ca. 12,2

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium
 Tel: 32-3-766.60.20 - Fax: 32-3-778.16.56 – E-mail: mail@wynns.eu – Website: www.wynns.eu

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.



Product specifications

Directions

- ✓ Shake contents well and add to the cooling system via the expansion tank if part of the system circuit (2 hoses: out and return), or directly into the radiator if a single hose overflow tank is fitted.
- ✓ For higher performance, first replace the old coolant by water, then add Wynn's Radiator Flush.
- ✓ Warm up the engine with the heater control in HOT position.
- ✓ Let the engine run at idle for 10 minutes. Heater still in "hot" position.
- ✓ Stop the engine and allow to cool, open drain valve and empty the system.
- ✓ With system still open, flush with water until clear, close system and refill with coolant.
- ✓ One bottle of 325 ml treats a system of 5 to 12 litres.
- ✓ Add Wynn's Radiator Stop Leak as a leak preventive agent.

Packaging

PN 56064 – 12x325 ml – EN
 PN 56072 – 12x325 ml – PL/HU/EL/PT/ES

Note

In case of cooling systems with cooling liquid filters, disconnect this device during the cleaning operation.

Wynn's Belgium bvba – Industriepark West 46 – B-9100 Sint-Niklaas / Belgium
 Tel: 32-3-766.60.20 - Fax: 32-3.778.16.56 – E-mail: mail@wynns.eu – Website: www.wynns.eu

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.