



# WYNN'S EXTREME POWER 0W40

TECHNICAL DATA SHEET

## DESCRIPTION

**WYNN'S EXTREME POWER 0W40** is a 100% synthetic lubricant formulated with synthetic base stock and latest generation additives for petrol and diesel engines requiring the highest performance under the most extreme conditions of use.

It is an ideal lubricant for extended drain intervals according to the instructions of each OEM, oriented to preserve the environment.

Its specific viscosity and exclusive additive composition ensure an optimum wear and oxidation protection in the widest temperature range of use, preventing the formation of deposits that reduce the lubricant life and compromise the vehicle performance.

## FEATURES

- **WYNN'S EXTREME POWER 0W40** has been conceived as a synthetic lubricant especially suitable for high-end vehicles with gasoline or diesel engines of very high performance, for use in the most extreme temperature conditions.
- The specific additive formula against friction, wear and oxidation ensures a satisfactory performance for longer periods than other lubricants of similar nature under any driving condition (motorway, urban traffic), both in summer and winter times, thanks to its superior resistance to build-up of deposits, sludge and varnish..
- The synthetic nature imparts an excellent pumpability and oil circulation even at very low temperatures, preventing an excessive wear of engine critical parts in cold conditions.

## QUALITY LEVEL

ACEA	A3/B4
API	SN/CF

## REFERENCES AND PACKAGING

77974	1L
77976	4L



# WYNN'S EXTREME POWER 0W40

## TECHNICAL DATA SHEET

### TECHNICAL CHARACTERISTICS

Property	Unit	Method	Value
Colour	-	Visual	Amber
Grade	-	SAE J300	0W-40
Density @ 15°C	g/ml	ASTM D4052	0.85
Kinematic Viscosity @ 100°C	cSt	ASTM D445	12.5 – 16.3
Kinematic Viscosity @ 40°C	cSt	ASTM D445	75
Viscosity Index	-	ASTM D2270	190
Dynamic Viscosity @ -30°C	cP	ASTM D5293	< 6,600
Dynamic Viscosity HTHS @ 150°C	cP	CEC-L- 36-90	> 3.5
T.B.N.	mg KOH/g	ASTM D2896	7
NOACK Volatility (250 °C, 1h)	%	CEC L-40-93	< 12
Flash Point	°C	ASTM D92	> 210
Pour Point	°C	ASTM D97	< -40

Note: These data represent average values after different tests. WYNN'S reserves the right to modify or update this record without prior notice.

### DIRECTIONS FOR USE AND PRECAUTIONS

- Lubricant with no specific health risks.
- Recommended use of protective gloves and safety glasses when using the product as universal protection precautions. In case of contact with skin or eyes, wash with plenty of water.
- The MSDS may be obtained upon request (+34 943 410 400).
- Dispose of contents/container to an authorised waste collection point.