



WYNN'S LONG LIFE 04 5W30

DESCRIPTION

WYNN'S LONG LIFE 04 5W30 is a 100% synthetic lubricant formulated with synthetic base stock and latest generation additives for petrol and diesel engines requiring an extended drain "Long Life" lubricant with optimal protection of the exhaust treatment systems.

It is an ideal lubricant for extended drain intervals according to the instructions of each OEM, oriented to preserve the environment.

The exclusive "low-mid SAPS" ensures a reduced content in sulphated ash, sulphur and phosphorus for an ideal compatibility with the DPF and catalyst devices (petrol TWC or diesel DOC) in vehicles prioritizing the reduction of emissions.

FEATURES

- **WYNN'S LONG LIFE 04 5W30** possesses a unique, synthetic composition designed for use as universal, "Long Life" lubricant. The specific additive formula against friction, wear and oxidation ensures a satisfactory performance for longer periods than other lubricants of similar nature under any driving condition (motorway, urban traffic), both in summer and winter times, thanks to its superior resistance to build-up of deposits, sludge and varnish.
- With a reduced content in sulphated ashes due to its "Low-Mid SAPS" character, it allows an optimal protection of the DPF + catalyst (DPF, DOC), avoiding any performance loss and the increase of fuel consumption due to the build-up of particles in the exhaust treatment systems.
- The use of BMW Longlife-04 specification is compulsory in BMW diesel vehicles equipped with DPF and can also be used in all petrol/diesel models of former generations, with the exception of "M" series.

NIVEL DE CALIDAD

ACEA	C3, (A3/B4)
API	SN/CF
BMW	LL-04
MERCEDES BENZ	229.51
VOLKSWAGEN	502.00/505.01
GM	DEXOS 2

REFERENCES AND PACKAGING

77914	1L
77915	5L
77910	208L



WYNN'S LONG LIFE 04 5W30

TECHNICAL DATA SHEET

TECHNICAL CHARACTERISTICS

Property	Unit	Method	Value
Colour	-	Visual	Amber
SAE Grade	-	SAE J300	5W-30
Density @ 15°C	g/ml	ASTM D4052	0.85
Kinematic Viscosity @ 100°C	cSt	ASTM D445	9.3 – 12.5
Kinematic Viscosity @ 40°C	cSt	ASTM D445	70
Viscosity Index	-	ASTM D2270	> 160
Dynamic Viscosity @ -30°C	cP	ASTM D5293	< 6,600
Dynamic Viscosity HTHS @ 150°C	cP	CEC-L- 36-90	> 3.5
T.B.N.	mg KOH/g	ASTM D2896	> 6.5
NOACK Volatility (250 °C, 1h)	%	CEC L-40-93	< 12
Flash Point	°C	ASTM D92	> 210
Pour Point	°C	ASTM D97	< -35

Note: These data represent average values after different tests. WYNN'S reserves the right to modify or update this record without prior notice.

DIRECTIONS FOR USE AND PRECAUTIONS

- Lubricant with no specific health risks.
- Recommended use of protective gloves and safety glasses when using the product as universal protection precautions. In case of contact with skin or eyes, wash with plenty of water.
- The MSDS may be obtained upon request (+34 943 410 400).
- Dispose of contents/container to an authorised waste collection point.