



WYNN'S LONG LIFE ECO ENERGY 5W30

TECHNICAL DATA SHEET

DESCRIPTION

WYNN'S LONGLIFE ECO ENERGY 5W30 is a 100% synthetic lubricant of low viscosity formulated with synthetic base stock and latest generation additives for petrol and diesel engines with specific Fuel Economy FE requirements, subsequently with lower environmental impact thanks to the reduction of CO₂ emissions to the atmosphere.

Its "mid SAPS" nature converts it in an ideal lubricant for all those direct injection petrol/diesel engines equipped with particle filters DPF and catalysts (TWC, DOC) and exhaust treatment systems.

Specific lubricant for PSA vehicles (Peugeot, Citroën) requiring the ACEA C2 quality level, also applicable to other OEMs with similar requests (Renault, Ford, Honda, Toyota, Mitsubishi).

FEATURES

- **WYNN'S LONGLIFE ECO ENERGY 5W30** has been specifically developed for offering superior Fuel Economy compared with similar lubricants, reducing hence the environmental impact responsible for the global warming.
- Exclusive additive package for an optimal protection against friction and wear, ensuring the additional Fuel Economy.
- Excellent performance in cold start-up thanks to its low viscosity.
- The exclusive "mid SAPS" technology (low content of sulphated ash, sulphur and phosphorus) ensures an optimal protection of the DPF filter and catalyst (TWC, DOC), avoiding any performance loss or increase of fuel consumption due to the build-up of the particles of the exhaust treatment systems.
- Especially suitable for PSA vehicles (Peugeot, Citroën) with ACEA C2 quality level.

QUALITY LEVEL

ACEA	C2, (A5/B5)
API	SN/CF

REFERENCES AND PACKAGING

77924	1L
77925	5L



WYNN'S LONG LIFE ECO ENERGY 5W30

TECHNICAL DATA SHEET

TECHNICAL CHARACTERISTICS

Property	Unit	Method	Value
Colour	-	Visual	Amber
SAE Grade	-	SAE J300	5W-30
Kinematic Viscosity @ 100°C	cSt	ASTM D445	9.3 – 12.5
Kinematic Viscosity @ 40°C	cSt	ASTM D445	72
Viscosity Index	-	ASTM D2270	> 160
Dynamic Viscosity @ -30°C	cP	ASTM D5293	< 6,600
Dynamic Viscosity HTHS @ 150°C	cP	CEC-L- 36-90	> 2.9
T.B.N.	mg KOH/g	ASTM D2896	> 6.0
NOACK Volatility (250 °C, 1h)	%	CEC L-40-93	< 12
Flash Point	°C	ASTM D92	> 210
Pour Point	°C	ASTM D97	< -35

Note: These data represent average values after different tests. WYNN'S reserves the right to modify or update this record without prior notice.

DIRECTIONS FOR USE AND PRECAUTIONS

- Lubricant with no specific health risks.
- Recommended use of protective gloves and safety glasses when using the product as universal protection precautions. In case of contact with skin or eyes, wash with plenty of water.
- The MSDS may be obtained upon request (+34 943 410 400).
- Dispose of contents/container to an authorised waste collection point.