



# WYNN'S 5W30 LONG LIFE GOLD VW 504/507

TECHNICAL DATA SHEET

## DESCRIPTION

**WYNN'S 5W30 LONGLIFE GOLD 504/507** is a 100% synthetic lubricant formulated with synthetic base stock and latest generation additives for petrol and diesel engines of the VAG Group (Audi, VW, Seat, Skoda) requiring the fulfilment of their extended drain specification 504.00/507.00, also applicable to other OEMs with similar requirements (BMW LL-04, Mercedes Benz 229.51).

It is the ideal lubricant for all direct injection petrol/diesel engines equipped with DPF filters and catalysts (TWC, DOC) in the exhaust treatment systems, for which the reduction of emissions and fuel consumption is a priority.

## FEATURES

- **WYNN'S 5W30 LONGLIFE GOLD 504/507** has been developed for use as universal lubricant for extended drain intervals in all petrol/diesel of the VAG Group incorporating exhaust treatment systems (DPF + TWC/DOC) and latest generation pump injectors.  
The only exception are the VAG Group engines I5 and V10 TDI and those equipped with standard drain pump injectors (1998 and before).
- It fulfils the requirements of the WIV system of VW vehicles and other Top Tier OEMs such as BMW (Long Life 04) and MERCEDES BENZ (229.51) for drain intervals up to 50.000 km or two years in diesel engines.
- The exclusive "Low SAPS" formula (low content in sulphated ash, sulphur and phosphorus) ensures an optimal protection of the DPF + TWC/DOC, avoiding any performance loss or increase of fuel consumption due to the particle accumulation in the exhaust treatment systems.
- The sophisticated composition allows the use of this lubricant in vehicles requiring ACEA C2 level.

## QUALITY LEVEL

ACEA	C3, (A3/B4)
VOLKSWAGEN	504.00/507.00
BMW	LL-04
MERCEDES BENZ	229.51
PORSCHE	C30

## REFERENCES AND PACKAGING

77904	1L
77905	5L
77900	208L



# WYNN'S 5W30 LONG LIFE GOLD VW 504/507

## TECHNICAL DATA SHEET

### TECHNICAL CHARACTERISTICS

Property	Unit	Method	Value
Colour	-	Visual	Amber
SAE Grade	-	SAE J300	5W-30
Density @ 15°C	g/ml	ASTM D4052	0.85
Kinematic Viscosity @ 100°C	cSt	ASTM D445	9.3 – 12.5
Kinematic Viscosity @ 40°C	cSt	ASTM D445	75
Viscosity Index	-	ASTM D2270	> 155
Dynamic Viscosity @ -30°C	cP	ASTM D5293	< 6,600
Dynamic Viscosity HTHS @ 150°C	cP	CEC-L- 36-90	> 3.5
T.B.N.	mg KOH/g	ASTM D2896	> 6.0
NOACK Volatility (250 °C, 1h)	%	CEC L-40-93	< 10
Flash Point	°C	ASTM D92	> 210
Pour Point	°C	ASTM D97	< -35

Note: These data represent average values after different tests. WYNN'S reserves the right to modify or update this record without prior notice.

### DIRECTIONS FOR USE AND PRECAUTIONS

- Lubricant with no specific health risks.
- Recommended use of protective gloves and safety glasses when using the product as universal protection precautions. In case of contact with skin or eyes, wash with plenty of water.
- The MSDS may be obtained upon request (+34 943 410 400).
- Dispose of contents/container to an authorised waste collection point.