



WYNN'S LONG LIFE RN 5W30

TECHNICAL DATA SHEET

DESCRIPTION

WYNN'S LONGLIFE RN 5W30 is a 100% synthetic lubricant of low viscosity formulated with synthetic base stock and latest generation additives for petrol and diesel engines requiring ACEA C4 quality level. Its characteristic "low SAPS" profile certifies a minimal generation of ashes, particularly suitable for engines equipped with particulate filters DPF and catalysts (petrol TWC, diesel DOC) in their exhaust treatment systems. Therefore, it is the right lubricant for RENAULT diesel vehicles designed under their own RN0720 specification. In the same way, it is a "long Life" lubricant permitting the extension of the drain intervals, always according to the OEM indications.

FEATURES

- **WYNN'S LONGLIFE RN 5W30** has been developed for its use as the specific lubricant in RENAULT diesel engines requiring the fulfilment of the RENAULT RN0720 specification.
- The exclusive "Long Life" profile optimizes the resistance against oxidation, allowing extra-long drain intervals.
- The "low SAPS" character (low content of sulphated ashes, sulphur, phosphorus designed for vehicles with ACEA C4 quality level implies a superior durability of the particulate filter and catalyst, with the subsequent reduction of contaminant emissions into the atmosphere.
- The combination of both properties secures a privileged care of the environment, with minimal contaminant emissions.

QUALITY LEVEL

ACEA	C4
RENAULT	RN-0720

REFERENCES AND PACKAGING

77955	5L
-------	----



WYNN'S LONG LIFE RN 5W30

TECHNICAL DATA SHEET

TECHNICAL CHARACTERISTICS

Property	Unit	Method	Value
Colour	-	Visual	Amber
SAE Grade	-	SAE J300	5W-30
Density @ 15°C	g/ml	ASTM D4052	0.85
Kinematic Viscosity @ 100°C	cSt	ASTM D445	9.3 – 12.5
Kinematic Viscosity @ 40°C	cSt	ASTM D445	70
Viscosity Index	-	ASTM D2270	> 160
Dynamic Viscosity @ -30°C	cP	ASTM D5293	< 6,600
Dynamic Viscosity HTHS @ 150°C	cP	CEC-L- 36-90	> 3.5
T.B.N.	mg KOH/g	ASTM D2896	> 6.0
NOACK Volatility (250 °C, 1h)	%	CEC L-40-93	< 12
Flash Point	°C	ASTM D92	> 210
Pour Point	°C	ASTM D97	< -35

Note: These data represent average values after different tests. WYNN'S reserves the right to modify or update this record without prior notice.

DIRECTIONS FOR USE AND PRECAUTIONS

- Lubricant with no specific health risks.
- Recommended use of protective gloves and safety glasses when using the product as universal protection precautions. In case of contact with skin or eyes, wash with plenty of water.
- The MSDS may be obtained upon request (+34 943 410 400).
- Dispose of contents/container to an authorised waste collection point.