



WYNN'S 5W40 PLUS COMPETITION

TECHNICAL DATA SHEET

DESCRIPTION

WYNN'S 5W40 PLUS COMPETITION is a 100% synthetic lubricant formulated with synthetic base stock and latest generation additives for all types of petrol and diesel engines.

This lubricant is adequate for extended drain intervals, always according to the instructions of each OEM. The exclusive additive composition ensures an optimal protection against wear and oxidation, preventing the build-up of deposits responsible of the reduction of the lubricant life cycle and the overall performance of the vehicle.

Therefore, it possesses a great versatility of use for the majority of OEMs.

FEATURES

- **WYNN'S 5W40 PLUS COMPETITION** has been designed as a multifunctional, synthetic lubricant of great versatility in all types of petrol and diesel engines (both naturally aspirated and turbo-fed).
- The specific additive combination against wear and oxidation ensures a satisfactory performance for longer periods than those provided by other lubricants of similar nature under any driving condition (motorway, urban traffic) both in summer and winter, thanks to its superior resistance against the build-up of deposits, sludge and varnish.
- The synthetic nature imparts an excellent pumpability and oil circulation even at very low temperatures, preventing an excessive wear of engine critical parts in cold conditions.

QUALITY LEVEL

ACEA	A3/B4
API	SN/CF
MERCEDES BENZ	229.31
VOLKSWAGEN	502.00/505.00
RENAULT	0700/0710

REFERENCES AND PACKAGING

77804	1L
77805	5L
77800	208L



WYNN'S 5W40 PLUS COMPETITION

TECHNICAL DATA SHEET

TECHNICAL CHARACTERISTICS

Property	Unit	Method	Value
Colour	-	Visual	Amber
Grade	-	SAE J300	5W-40
Density @ 15°C	g/ml	ASTM D4052	0.85
Kinematic Viscosity @ 100°C	cSt	ASTM D445	12.5 – 16.3
Kinematic Viscosity @ 40°C	cSt	ASTM D445	85
Viscosity Index	-	ASTM D2270	> 160
Dynamic Viscosity @ -30°C	cP	ASTM D5293	< 6,600
Dynamic Viscosity HTHS @ 150°C	cP	CEC-L- 36-90	> 3.5
T.B.N.	mg KOH/g	ASTM D2896	10
NOACK Volatility (250 °C, 1h)	%	CEC L-40-93	< 12
Flash Point	°C	ASTM D92	> 210
Pour Point	°C	ASTM D97	< -35

Note: These data represent average values after different tests. WYNN'S reserves the right to modify or update this record without prior notice.

DIRECTIONS FOR USE AND PRECAUTIONS

- Lubricant with no specific health risks.
- Recommended use of protective gloves and safety glasses when using the product as universal protection precautions. In case of contact with skin or eyes, wash with plenty of water.
- The MSDS may be obtained upon request (+34 943 410 400).
- Dispose of contents/container to an authorised waste collection point.