



WYNN'S 75W80 GEAR SAVER

DESCRIPTION

WYNN'S 75W80 GEAR SAVER is a premium lubricant designed for fulfilling the requirements of any gear system working in conditions of extreme severity.

It is formulated with a selected set of additives that provide optimal performance at extreme pressures, high point loads, shocks, etc., with a satisfactory resistance to oxidation and excellent anti-wear properties. The high antifoaming properties ensure a smooth operation.

It is especially suited in all types of manual gearboxes, rear axles, differentials working under moderate and severe conditions mounted in all types of passenger cars, vans and transport fleets, trucks, earthmoving machinery, public works, etc.

Due to its special formulation, it can also be used in all types of industrial gearboxes with enclosed crankcase, as well as for the lubrication of bushings and bearings exposed to heavy workload conditions that require a API GL-5 lubricant.

FEATURES

- High Viscosity Index and low pour point.
- High load capacity (70lb. TIMKEN).
- High thermal stability and great resistance to aging, which guarantees its endurance under heavy loads and high temperatures.
- Reinforces properties against oxidation and corrosion.
- Excellent compatibility with most of the seals and elastomers.

QUALITY LEVEL

API	GL-5
MIL-L	2105-D
MACK TRUCKS	GO-G

REFERENCES AND PACKAGING

77864	1L
77865	5L
77867	20L



WYNN'S 75W80 GEAR SAVER

TECHNICAL DATA SHEET

TECHNICAL CHARACTERISTICS

Property	Unit	Method	Value
Colour	-	Visual	Amber
SAE Grade	-	SAE J306	75W80
Density @ 20°C	g/ml	ASTM D1475	0.875
Kinematic Viscosity @ 100°C	cSt	ASTM D445	7.8 - 8.2
Kinematic Viscosity @ 40°C	cSt	ASTM D445	45 - 55
Flash Point	°C	ASTM D92	200
Pour Point	°C	ASTM D97	-43
Foam @ 24°C (tendency/stability)	ml/ml	ASTM D892	<10/0 max.
Steel corrosion	-	ASTM D665B	Pass
Cu corrosion	-	ASTM D130	1 máx.
4 Balls – Weld Load	N	ASTM D2596	>300
TIMEKN Weld Load	Lb.	ASTM D2782	70

Note: These data represent average values after different tests. KRAFFT reserves the right to modify or update this record without prior notice.

DIRECTIONS FOR USE AND PRECAUTIONS

- Lubricant with no specific health risks.
- Recommended use of protective gloves and safety glasses when using the product as universal protection precautions. In case of contact with skin or eyes, wash with plenty of water.
- Dispose of contents/container to an authorised waste collection point.

Review date: 09.05.2017