



WYNN'S 80W90 GEAR SAVER

TECHNICAL DATA SHEET

DESCRIPTION

WYNN'S 80W90 GEAR SAVER is an extra high-performance commercial gear lubricant formulated with premium base stock and latest generation additives where the GL-5 quality level is required.

Suitable for on-highway light and heavy duty trucks, busses, vans and cars, but also for Off-highway industries including construction, mining, quarrying and agriculture.

Recommended for industrial applications involving hypoid and other gears operating under severe conditions: high speed, shocks, very high or low torque.

FEATURES

- WYNN'S 80W90 GEAR SAVER is a specifically engineered high performance lubricant for heavy duty transmissions, axles and final drives requiring GL-5 level performance.
- Smooth, durable performance and excellent wear protection.
- Its adequate Viscosity Index provides highly stability when exposed to severe heat, oxidation and shearing.
- Good protection against low speed/high torque wear and against high speed scoring.
- Good resistance to foaming.
- Compatible with typical automotive seals and gaskets.

QUALITY LEVEL

API	GL-5
MIL-L	2105D
ZF	TE-ML 05A/07A/08/12E/16B/16/C/16D/17B/19B/21A
MAN	342 Type M-2
SCANIA	STO 1:0

REFERENCES AND PACKAGING

77854	1L
77855	5L
77857	20L
77870	2008L

TECHNICAL CHARACTERISTICS

Property	Unit	Method	Value
Colour	-	Visual	Amber
SAE grade	-	SAE J306	80W90
Density @ 20°C	g/ml	ASTM D4052	0.90
Kinematic Viscosity @ 100°C	cSt	ASTM D445	13.5 – 18.5
Kinematic Viscosity @ 40°C	cSt	ASTM D445	140
Max. Temperature @ 150,000 cP	°C	ASTM D2983	< -26
Flash Point	°C	ASTM D92	> 215
Pour Point	°C	ASTM D97	< -21

Note: These data represent average values after different tests. KRAFFT reserves the right to modify or update this record without prior notice.

DIRECTIONS FOR USE AND PRECAUTIONS

- Lubricant with no specific health risks.
- Recommended use of protective gloves and safety glasses when using the product as universal protection precautions. In case of contact with skin or eyes, wash with plenty of water.
- The MSDS may be obtained upon request (+34 943 410 400).
- Dispose of contents/container to an authorised waste collection point.

Review date: 14.03.2017