



WYNN'S ATF DEXRON-II

DESCRIPTION

WYNN'S ATF DEXRON-II is a multi-purpose mineral ATF designed specifically for automatic transmissions, servo-mechanisms, torque converters, power steering systems, etc. of passenger cars, commercial vehicles and buses that require fluids of DEXRON II quality level, and for the OEM specifications listed below.

It is suitable for large fleets of different vehicles where a single, ATF is required for general use.

FEATURES

- Low boiling and freezing points allow a fast circulation and exceptional lubrication at low temperatures.
- Its superior level of protection against wear extends the useful lifetime of transmissions.
- Compatible with the seals and other materials used in transmission manufacturing.
- Excellent protection against corrosion and foam formation.

TECHNICAL CHARACTERISTICS

Property	Unit	Method	Data
Colour	-	Visual	Red
Density at 20°C	g/ml	ASTM D4052	0.87
SAF grade	-	SAE J300	10W
Kinematic viscosity @ 100°C	mm ² /s (cSt)	ASTM D445	7.1
Kinematic viscosity @ 40°C	mm ² /s (cSt)	ASTM D445	38.5
Viscosity index	-	ASTM D2270	155
Freezing point	°C	ASTM D97	-35

Note: These data are average figures after several tests. WYNN'S reserves the right to change or update this data file without prior notice.

REFERENCES AND PACKAGING

77964

1L



WYNN'S ATF DEXRON-II

TECHNICAL DATA SHEET TECHNICAL DATA SHEET

QUALITY LEVEL

GM	DEXRON-IID
ZF	TE-ML 03D, 04D,09, 05L, 11A, 14A, 17C
Voith	H55.6335.XX
MAN	339 Type V-1, Z-1
Mercedes-Benz	MB 236.3
Volvo	97335

DIRECTIONS FOR USE AND PRECAUTIONS

- It is always advisable to empty the automatic transmission when changing the lubricant. Do not top up.
- Goggles and gloves should be used during application as general protective measures. In case of contact with skin or eyes, wash with abundant water.
- Dispose of contents/containers at an authorised waste collection point.

Review date: 25.04.2017